

SPECIFICATIONS:

- 1.VOLTAGE/CURRENT RATING: 30V/0.3A AC;
- 2.WITHSTANDING VOLTAGE: 100V AC ONE MINUTE;
- 3.INSULATION RESISTANCE: 50M Ω MIN;
- 4.CONTACT RESISTANCE: 100m Ω MAX;
- 5.OPERATING TEMPERATURE RANGE: -35° C TO 85° C.


MATERIAL:

- 1.INSULATOR: LCP UL 94V-0 BLACK;
- 2.TERMINAL: COPPER ALLOY;
- 3.METAL FITTINGS: COPPER ALLOY.

PLATING:

- 1.TERMINAL: GOLD PLATING,
NICKEL 50 μ " MIN. OVER ALL;
- 2.METAL FITTINGS: TIN 100 μ " MIN. OVER NICKEL 50 μ "MIN.

04 n H08 P



PIN NO.	A	B	C
10	3.80	3.20	1.60
12	4.20	3.60	2.00
16	5.00	4.40	2.80
20	5.80	5.20	3.60
24	6.60	6.00	4.40
30	7.80	7.20	5.60
34	8.60	8.00	6.40
40	9.80	9.20	7.60
50	11.80	11.20	9.60

△	DATE	ECR	东莞市创亿科技有限公司 DONGGUAN CYCONN TECHNOLOGY CO.,LTD				PART NAME: BTB 0.4mm Plug				S/C NO	TOLERANCE:		
			APPROVED	CHECKED	DRAWING	DWG NO.	DATE	REV	SCALE	UNIT	SHEET	⊕	.XX ±0.20	
								A	FIT	mm	10F1		.XXX ±0.10	