



孔位 poles	A	B	C	孔位 poles	A	B	C	孔位 poles	A	B	C	孔位 poles	A	B	C
3	2.00	6.50	4.10	14	13.00	17.50	15.10	25	24.00	28.50	26.10	36	35.00	39.50	37.10
4	3.00	7.50	5.10	15	14.00	18.50	16.10	26	25.00	29.50	27.10	37	36.00	40.50	38.10
5	4.00	8.50	6.10	16	15.00	19.50	17.10	27	26.00	30.50	28.10	38	37.00	41.50	39.10
6	5.00	9.50	7.10	17	16.00	20.50	18.10	28	27.00	31.50	29.10	39	38.00	42.50	40.10
7	6.00	10.50	8.10	18	17.00	21.50	19.10	29	28.00	32.50	30.10	40	39.00	43.50	41.10
8	7.00	11.50	9.10	19	18.00	22.50	20.10	30	29.00	33.50	31.10				
9	8.00	12.50	10.10	20	19.00	23.50	21.10	31	30.00	34.50	32.10				
10	9.00	13.50	11.10	21	20.00	24.50	22.10	32	31.00	35.50	33.10				
11	10.00	14.50	12.10	22	21.00	25.50	23.10	33	32.00	36.50	34.10				
12	11.00	15.40	13.10	23	22.00	26.50	24.10	34	33.00	37.50	35.10				
13	12.00	16.50	14.10	24	23.00	27.50	25.10	35	34.00	38.50	36.10				

东莞市创亿科技有限公司			1.0-1 -nPW	
表注公差	尺寸公差: ±0.15mm	设计		图号
	角度公差: ±3°	审查		比例 ITE
		核准		单位 mm
		供应商	GYCONN	页次 of